



— GROUND CONTROL • DEFENSE HANDHELD

C-SROC

A ruggedized, NDAA-compliant handheld GCS on the Samsung Galaxy Active Tab 5 (Tactical) — hot-swap power, swappable radio modules, and Nett Warrior built in.



8" WUXGA
750-NIT

MIL-810H
IP65

AES-256
STIG

927 G
HANDHELD

NETT WARRIOR
EUD



SOLDIER ROBOTIC CONTROLLER.

Standardized defense control, uncompromising persistence — a ruggedized handheld GCS built on the Samsung Galaxy Active Tab 5 (Tactical Edition), with soft-touch ABS, a 5D plus dual Hall-effect joysticks, and a 750-NIT glove-touch display.

Modular open-system architecture: hot-swappable SBM power, swappable SRM radio modules, and a Nett Warrior connector built into the handle — AES-256, STIG-compliant, NDAA Section 848.



02 - CONFIGURATION HIGHLIGHTS

8" 750-NIT DISPLAY	MIL-810H IP65	AES-256 STIG	Nett Warrior EUD	927 g HANDHELD
------------------------------	-------------------------	------------------------	----------------------------	--------------------------

03 — COMPATIBLE PLATFORMS

FLIES EVERY CARRIER PLATFORM.

MAVLINK-NATIVE • MOST THIRD-PARTY UAVS & AUTOPILOTS

		
H6 FAMILY ELECTRIC • HYDRONE • HYBRID EFI ■ 5–8 kg Payloads ■ Hex airframe • foldable ■ One frame • three power systems	CARRIER HX8 COAXIAL X8 OCTOCOPTER ■ 8 kg Payload ■ Motor redundancy ■ 21" payload bay	H4C QUAD COMPACT HEAVY-LIFT ■ 4 kg Payload ■ Folds to backpack size ■ <90 s deploy

■ SRM SLEDGE SWAPPABLE RADIOS • NETT WARRIOR CONNECTOR • EUD-COMPATIBLE

SPECIFICATIONS
TECHNICAL SPECIFICATIONS.

A DISPLAY & CONTROLS			
DISPLAY	8" Samsung Active Tab 5 Tactical Edition	PRIMARY JOYSTICK	1× 5D
TOUCH	10-pt Capacitive · Direct Bonding · AR · Glove	HALL-EFFECT JOYSTICKS	2× 2-Axis
OS	Android (or Windows)	AUX JOYSTICKS	2× 1-Axis
CPU	Qualcomm SDM660 · 2.2 GHz Octa-Core	BUTTON ARRAY	4× Push · 12× Bezel · 2× Presence
MEMORY	4 GB LPDDR4		

B POWER, COMMS, SECURITY & BUILD			
POWER	Hot-Swap Dynamically-Balancing SBM Slots	SECURITY	ARM® TrustZone®
RADIO	SRM Sledge · Swappable Radio Modules	COMPLIANCE	STIG-Compliant · NDAA Sec 848
TACTICAL PORT	Nett Warrior · EUD Compatible	FOUNDATION	Samsung Galaxy Active Tab 5 (Tactical)
USB	USB 3.0 Type-C Host (OTG / DP / HDMI)	DURABILITY	MIL-STD-810-H · IP65
ENCRYPTION	AES-256 (Available)	BUILD	256 × 140 × 68 mm · 927 g



HARRIS AERIAL

C-SROC

C-SROC • PRODUCT BROCHURE

C-SROC.

— CONTACT

WEB

harrisaerial.com

EMAIL

info@harrisaerial.com

PHONE

(407) 725-7886